


Circular Chart Recorders

Wagner Instrumentations 12" circular chart recorders are rugged, dependable and are available in numerous configurations to meet your every need. Recorders are available for recording any hydraulic function and come with multi-speed clocks in either battery operated or manual wind configurations.

Features:

- Recorder comes in 1, 2, and 3 pen versions and portable or panel mount versions.
- Can be calibrated for use with any type of hydraulic function up to 16000 psi straight pressure or 30,000 psi 4 x 1 deboosted pressure.
- Available with multi speed clocks in 1 hr., 4 hr., and 24 hr. versions and in battery operated or manual wind versions.
- Highly accurate, calibrated to within .5% accuracy.
- Available in Metric or English versions.
- Available with or without gauges built into base.
- Comes fully loaded ready to use right out of box, with disconnect set, 100 charts, and 1 spare pen per function.
- Optional ¼" high-pressure hose available (specify length when ordering).
- Optional diaphragm protector, 1:1 piston isolator or deboosters available (specify type needed, 1502 or 2202 union and sub, and standard or H2S service when ordering).



Benefits:

- Rugged design allows for years of accurate, dependable usage.
- Uses standard 6" fluid filled gauges so operations and maintenance are standard for the industry.
- Uses standard 12" charts, clip-on pens and Sonceboz brand clocks, so spare parts are interchangeable with most major recorder manufacturers.
- Recorder uses the same bourdon tube assemblies as standard 6" gauges, so the bourdon tube assemblies are interchangeable with standard 6" gauge assemblies.

To order specify:

- Pressure range or capacity to be recorded
- Manual wind or electric clock
- Clock speed (1 hr. 4hr. or 24 hr.)
- Wall (truck) mount or portable type.